



www.miko-plast.com

KONGSVEIEN 94 N-1177 OSLO NORWAY

TELEPHONE : + 47 23 38 47 73  
TELEFAX : + 47 23 38 47 71  
ENTERPRISE NO: 980 030 628

CORE PLUG 306 HD

Doc.7:16

PRODUCT DATA:

Core Ø ..... 306 mm  
Dimension insertion angle..... 298-304 mm  
Dimension ..... 304-306,5x 42 x80mm  
Dimension lock ribs ..... 309 mm  
Tolerance ..... +0,20- 0,40 mm  
Weight ..... 1010 gram  
Material ..... PEHD  
Alternative material..... PP  
Compression strength deformation 4mm ..... 18 KN  
Compression strength break/max ..... 28 KN  
Tolerance..... +- 2KN

PACKAGING:

Packing ..... Pallet  
Number each packing..... 240 pcs  
Net weight each packing ..... 300 kg

MATERIAL RECYCLING DATA HDPE:

Density ISO1183 ..... 962 kg/m<sup>3</sup>  
Melt index 190°C/2,16 kg ISO 1133 ..... 12 g/10min  
Tensile strength ISO 527-2 ..... 1150 Mpa  
Surface hardness ISO 868..... 62 Shore D  
Heat deflection ISO 75-2 ..... 73°C  
Impact strength ISO 8256\*/A1 ..... 50 KJ/m<sup>2</sup>