



www.miko-plast.com

KONGSVEIEN 94 N-1177 OSLO NORWAY

TELEPHONE : + 47 23 38 47 73  
TELEFAX : + 47 23 38 47 71  
ENTERPRISE NO: 980 030 628

**CORE PLUG 76 mm**

**Doc.7:7**

**PRODUCT DATA:**

Core Ø .....	76 mm
Dimension insertion angle.....	71-74 mm
Dimension .....	76,5 x 28 x 25 mm
Dimension lock ribs .....	78,5 mm
Tolerance.....	+ - 0,50 mm
Weight .....	38 gram
Material .....	PEHD
Alternative material.....	PP
Compression strength deformation .....	4 KN
Compression strength break .....	9 KN
Tolerance.....	+ - 1 KN

**PACKAGING:**

Packing.....	Octabin
Number each packing.....	7.500 pcs.
Net weight each packing .....	285 kg

**MATERIAL RECYCLING DATA HDPE:**

Density	ISO1183 .....	962 kg/m <sup>3</sup>
Melt index 190°C/2,16 kg	ISO 1133.....	12 g/10min
Tensile strength	ISO 527-2 .....	1150 Mpa
Surface hardness	ISO 868.....	62 Shore D
Heat deflection	ISO 75-2 .....	73°C
Impact strength	ISO 8256*/A1 .....	50 KJ/m <sup>2</sup>