



www.miko-plast.com

Østre Aker vei 22, N-0581 OSLO, NORWAY

TELEPHONE : + 47 23 38 47 73  
ENTERPRISE NO: 980 030 628

Miko Core Plug 150,7™

Doc.7:11

PRODUCT DATA :

Core Ø .....	150-150,7 mm
Dimension insertion angle.....	145-148 mm
Dimension .....	148-150,7 x 40 x 25 mm
Dimension lock ribs .....	153 mm
Tolerance.....	+ -0,4 mm
Weight .....	174,0 gram
Material .....	PEHD
Alternative material.....	PP
Compression strength deformation .....	7 KN
Compression strength break .....	12 KN
Tolerance.....	+ - 2 KN

PACKAGING:

Packing .....	Pallets
Number each packing.....	625 stk.
Netto weight each packing .....	150 kg

MATERIAL RECYCLING DATA HDPE:

Density	ISO1183 .....	962 kg/m <sup>3</sup>
Melt index 190°C/2,16 kg	ISO 1133.....	12 g/10min
Tensile strength	ISO 527-2 .....	1150 Mpa
Surface hardness	ISO 868.....	62 Shore D
Heat deflection	ISO 75-2 .....	73°C
Impact strength	ISO 8256*/A1 .....	50 KJ/m <sup>2</sup>