



**PLAST**

*www.miko-plast.com*

Østre Aker Vei 22, N-0581 OSLO, NORWAY

TELEPHONE : + 47 23 38 47 73  
ENTERPRISE NO: 980 030 628

**Miko Core Plug 302 mm HD™**

**Doc.7:15**

**PRODUCT DATA:**

Core Ø .....	302 mm
Dimension insertion angle.....	299-300,5 mm
Dimension .....	300,5-301,5x 42 x80mm
Dimension lock ribs .....	304 mm
Tolerance .....	+0,4 mm
Weight .....	1200 gram
Material .....	PEHD
Alternative material.....	PP
Compression strength deformation 4mm .....	18 KN
Compression strength break .....	28 KN
Tolerance.....	+ - 3KN

**PACKAGING:**

Packing .....	Pallet
Number each packing.....	240 pcs
Net weight each packing .....	288 kg

**MATERIAL RECYCLING DATA HDPE:**

Density	ISO1183 .....	962 kg/m3
Melt index 190°C/2,16 kg	ISO 1133.....	12 g/10min
Tensile strength	ISO 527-2 .....	1150 Mpa
Surface hardness	ISO 868.....	62 Shore D
Heat deflection	ISO 75-2 .....	73°C
Impact strength	ISO 8256*/A1 .....	50 KJ/m2