



www.miko-plast.com

Østre Aker vei 22, N-0581 OSLO, NORWAY

TELEPHONE : + 47 23 38 47 73  
ENTERPRISE NO: 980 030 628

### Miko Core Plug 305mm L™

#### PRODUCT DATA:

Core Ø .....	305 mm
Dimension insertion angle.....	302-303,5 mm
Dimension .....	303,5-304,5x 42x 80mm
Dimension lock ribs .....	307 mm
Tolerance.....	+0,4 mm
Weight .....	910 gram
Material .....	PEHD
Alternative material.....	PP
Compression strength deformation 4mm .....	18 KN
Compression strength break .....	28 KN
Tolerance.....	+ 3KN

#### PACKAGING:

Packing .....	Pallet
Number each packing .....	250 pcs
Net weight each packing .....	228 kg

#### MATERIAL RECYCLING DATA HDPE:

Density	ISO1183 .....	962 kg/m <sup>3</sup>
Melt index 190°C/2,16 kg	ISO 1133.....	12 g/10min
Tensile strength	ISO 527-2 .....	1150 Mpa
Surface hardness	ISO 868.....	62 Shore D
Heat deflection	ISO 75-2 .....	73°C
Impact strength	ISO 8256*/A1 .....	50 KJ/m <sup>2</sup>