



PLAST

www.miko-plast.com

Østre Aker Vei 22, N-0581 OSLO, NORWAY

TELEPHONE : + 47 23 38 47 73
ENTERPRISE NO: 980 030 628

Miko Core Plug 306,5™

Art. No: P-306-002

Doc.8:17

PRODUCT DATA:

| | |
|--|---------------------|
| Core Ø | 306 mm |
| Dimension insertion angle..... | 298-304 mm |
| Dimension | 304-306,5x 42 x80mm |
| Dimension lock ribs | 309 mm |
| Tolerance..... | +0,20- 0,40 mm |
| Weight | 930 gram |
| Material | PEHD |
| Alternative material..... | PP |
| Compression strength deformation 4mm | 18 KN |
| Compression strength break/max | 28 KN |
| Tolerance..... | + - 2KN |

PACKAGING:

| | |
|--|---------|
| Packing | Pallet |
| Number each packing..... | 250 pcs |
| Number each transport unit (Two pallets) | 500 pcs |
| Net weight each packing | 250 kg |

MATERIAL RECYCLING DATA HDPE:

| | | |
|--------------------------|--------------------|------------|
| Density | ISO1183 | 962 kg/m3 |
| Melt index 190°C/2,16 kg | ISO 1133..... | 12 g/10min |
| Tensile strength | ISO 527-2 | 1150 Mpa |
| Surface hardness | ISO 868..... | 62 Shore D |
| Heat deflection | ISO 75-2 | 73°C |
| Impact strength | ISO 8256*/A1 | 50 KJ/m2 |